

## 20 Liter Refrigerated Circulator, -30°C



SD20R-30

### Key Specifications

<b>Description</b>	-30, 20 L Ref. Circulator
<b>Controller Type</b>	Standard Digital
<b>Display</b>	3.75" Touch-Pad LCD
<b>Connectivity</b>	RS232
<b>Swivel 180 Rotating Controller</b>	Yes
<b>Working Temperature Range °C</b>	-30° to 170°
<b>Temperature Stability °C</b>	±0.04°
<b>Fluid Optimization/Specific Heat Tuning</b>	Automatic
<b>Temperature Calibration Capability</b>	1-point
<b>Working Access (L x W x D) (cm)</b>	25 x 31.6 x 14 cm
<b>Pump Type</b>	Pressure
<b>Flammability Class (DIN 12876-1)</b>	I (NFL)
<b>Electrical Plug Options</b>	Part numbers listed are Standard U.S. and European types. <a href="#">Country specific plug types available.</a> Contact your <a href="#">regional distributor to order.</a>

### Key Features

# Standard Digital Controller

## Key Features

- Large, universal icon and English display
- Swivel 180™ Rotating Controller
- On-board connectivity: RS-232 serial output
- On-screen prompts
- Automatic performance optimization
- Single-point calibration capability

## Common Specifications

<b>Working Temperature Range °F</b>	-22° to 338°
<b>Working Temperature Range °C</b>	-30° to 170°
<b>Nominal Cooling Capacity @ +20C (W)</b>	915
<b>Reservoir Capacity (gallons)</b>	5.28
<b>Reservoir Capacity (liters)</b>	20
<b>Reservoir/Tank Material</b>	Stainless Steel
<b>Reservoir Cover</b>	Included
<b>DuraTop</b>	Yes
<b>LidDock</b>	Yes
<b>Cleanable Air Filter</b>	Yes
<b>Working Access (L x W x D) (inches)</b>	9.85 x 12.45 x 5.5 in
<b>Working Access (L x W x D) (cm)</b>	25 x 31.6 x 14 cm
<b>Temperature Stability °F</b>	±0.08°
<b>Temperature Stability °C</b>	±0.04°
<b>Display</b>	3.75" Touch-Pad LCD
<b>Display Resolution (Set)</b>	0.1
<b>Display Resolution (Read)</b>	0.1
<b>Pump Type</b>	Pressure
<b>Pump Speed</b>	Two
<b>Process Connections</b>	1/4" (F) NPT
<b>Flammability Class (DIN 12876-1)</b>	I (NFL)
<b>Over-Temperature Protection / Failsafe Heater Control</b>	Yes
<b>Low Liquid Level Protection</b>	Yes
<b>WhisperCool Environmental Control Technology</b>	Yes
<b>Cool Command Refrigeration Technology</b>	Yes
<b>Reservoir Drain</b>	Yes

<b>Maximum Ambient Temperature °F</b>	95°
<b>Maximum Ambient Temperature °C</b>	35°
<b>Overall Dimensions (L x W x H) (inches)</b>	24 x 16.6 x 26.9 in
<b>Overall Dimensions (L x W x H) (cm)</b>	61 x 41.9 x 68.3 cm
<b>Refrigerant</b>	R404A
<b>Environmental Compliance</b>	RoHS, WEEE
<b>Shipping Weight (pounds)</b>	130.0
<b>Shipping Weight (kilograms)</b>	58.9
<b>Catalog Page Number</b>	42-43

## 60 Hz Only

<b>Part Number</b>	SD20R-30-A11B
<b>Maximum Pressure (psi)</b>	3.5
<b>Maximum Pressure (bar)</b>	0.24
<b>Maximum Pressure Flow Rate (gpm)</b>	2.90
<b>Maximum Pressure Flow Rate (l/min)</b>	11.0
<b>Cooling Capacity @ -20°C (W)</b>	165
<b>Cooling Capacity @ 0°C (W)</b>	505
<b>Cooling Capacity @ +20°C (W)</b>	915
<b>Cooling Capacity @ +100°C (W)</b>	915
<b>Included Hardware</b>	Nylon hose adapters for 3/8", 1/4", and 3/16"
<b>Heater Wattage</b>	1100
<b>Electrical Requirements (VAC/Hz/Ph/A)</b>	120/60/1/13
<b>Regulatory Approvals</b>	ETL

## 50 Hz Only

<b>Part Number</b>	SD20R-30-A12E
<b>Maximum Pressure (psi)</b>	2.9
<b>Maximum Pressure (bar)</b>	0.20
<b>Maximum Pressure Flow Rate (gpm)</b>	2.70
<b>Maximum Pressure Flow Rate (l/min)</b>	10.2
<b>Cooling Capacity @ -20°C (W)</b>	165
<b>Cooling Capacity @ 0°C (W)</b>	505
<b>Cooling Capacity @ +20°C (W)</b>	915
<b>Cooling Capacity @ +100°C (W)</b>	915
<b>Included Hardware</b>	Nylon hose adapters for 3/8", 1/4", and 3/16", and 1/4" NPT to M16 adapter
<b>Heater Wattage</b>	2200
<b>Electrical Requirements (VAC/Hz/Ph/A)</b>	240/50/1/13



© 2015-2020 **PolyScience** 6600 W. Touhy Avenue, Niles, Illinois 60714-4516 USA

**Phone:** +1(847) 647-0611 or +1(800) 229-7569 **Fax:** +1(847) 647-1155

\*/

**Source URL (modified on 09/16/2020 - 07:46):** <https://polyscience.com/circulating-baths/20-liter-refrigerated-circulator-30%C2%B0c-3>