

## 28 Liter Heated Circulator



AD28H200

### Key Specifications

<b>Description</b>	200, 28 L Htg. Circulator
<b>Controller Type</b>	Advanced Digital
<b>Display</b>	3.75" Touch-Pad LCD
<b>Connectivity</b>	Ethernet, USB A & B, RS232/addressable RS485, External Temperature Probe
<b>Languages Supported</b>	4: French, German, Spanish, English
<b>Swivel 180 Rotating Controller</b>	Yes
<b>Working Temperature Range °C</b>	Ambient +10° to 200°
<b>Temperature Stability °C</b>	±0.01°
<b>Fluid Optimization/Specific Heat Tuning</b>	Automatic and/or user-adjustable
<b>Temperature Calibration Capability</b>	1-point
<b>Working Access (L x W x D) (cm)</b>	31.4 x 35.9 x 14 cm
<b>Pump Type</b>	Pressure/Suction
<b>External Temperature Control Capability</b>	Yes
<b>Flammability Class (DIN 12876-1)</b>	III (FL)

### Key Features

# Advanced Digital Controller

## Key Features

- Intuitive 3.75" (9.5 cm) display with touch-pad control
- 4 languages: French, German, Spanish, English
- Swivel 180™ Rotating Controller
- On-board connectivity: USB-A & B, Ethernet, RS-232/RS-485 and external temperature probe
- On-screen prompts
- Automatic performance optimization and specific heat tuning
- Single-point calibration capability

## Common Specifications

<b>Working Temperature Range °F</b>	Ambient + 20° to 392°
<b>Working Temperature Range °C</b>	Ambient +10° to 200°
<b>Reservoir Capacity (gallons)</b>	7.4
<b>Reservoir Capacity (liters)</b>	28
<b>Reservoir/Tank Material</b>	Stainless Steel
<b>Reservoir Cover</b>	Included
<b>DuraTop</b>	Yes
<b>LidDock</b>	Yes
<b>Working Access (L x W x D) (inches)</b>	12.35 x 14.13 x 5.5 in
<b>Working Access (L x W x D) (cm)</b>	31.4 x 35.9 x 14 cm
<b>Temperature Stability °F</b>	±0.02°
<b>Temperature Stability °C</b>	±0.01°
<b>Display</b>	3.75" Touch-Pad LCD
<b>Display Resolution (Set)</b>	0.01
<b>Display Resolution (Read)</b>	0.01
<b>Pump Type</b>	Pressure/Suction
<b>Pump Speed</b>	Variable
<b>Process Connections</b>	1/4" (F) NPT
<b>External Temperature Control Capability</b>	Yes
<b>Flammability Class (DIN 12876-1)</b>	III (FL)
<b>Over-Temperature Protection / Failsafe Heater Control</b>	Yes
<b>Low Liquid Level Protection</b>	Yes
<b>Reservoir Drain</b>	Yes
<b>Cooling Coil</b>	Yes
<b>Included Software</b>	PolyTemp Viewer, USB driver
<b>Maximum Ambient Temperature °F</b>	95°
<b>Maximum Ambient Temperature °C</b>	35°
<b>Overall Dimensions (L x W x H) (inches)</b>	26.5 x 18 x 16.6 in
<b>Overall Dimensions (L x W x H) (cm)</b>	67.2 x 45.7 x 42.2 cm

<b>Environmental Compliance</b>	RoHS, WEEE
<b>Shipping Weight (pounds)</b>	82.0
<b>Shipping Weight (kilograms)</b>	37.1
<b>Catalog Page Number</b>	56-57

## 60 Hz Only

<b>Part Number</b>	AD28H200-A11B
<b>Maximum Pressure (psi)</b>	4.3
<b>Maximum Pressure (bar)</b>	0.30
<b>Maximum Pressure Flow Rate (gpm)</b>	5.30
<b>Maximum Pressure Flow Rate (l/min)</b>	20.1
<b>Maximum Suction Flow Rate (gpm)</b>	3.9
<b>Maximum Suction Flow Rate (l/min)</b>	14.7
<b>Included Hardware</b>	Nylon hose adapters for 3/8", 1/4", and 3/16"
<b>Heater Wattage</b>	1100
<b>Electrical Requirements (VAC/Hz/Ph/A)</b>	120/60/1/10
<b>Regulatory Approvals</b>	ETL

## 50 Hz Only

<b>Part Number</b>	AD28H200-A12E
<b>Maximum Pressure (psi)</b>	3.6
<b>Maximum Pressure (bar)</b>	0.25
<b>Maximum Pressure Flow Rate (gpm)</b>	4.40
<b>Maximum Pressure Flow Rate (l/min)</b>	16.7
<b>Maximum Suction Flow Rate (gpm)</b>	3.2
<b>Maximum Suction Flow Rate (l/min)</b>	12.2
<b>Included Hardware</b>	Nylon hose adapters for 3/8", 1/4", and 3/16", and 1/4" NPT to M16 adapter
<b>Heater Wattage</b>	2200
<b>Electrical Requirements (VAC/Hz/Ph/A)</b>	240/50/1/10
<b>Regulatory Approvals</b>	CE



© 2015-2020 **PolyScience** 6600 W. Touhy Avenue, Niles, Illinois 60714-4516 USA

**Phone:** +1(847) 647-0611 or +1(800) 229-7569 **Fax:** +1(847) 647-1155

\*/

**Source URL (modified on 12/26/2019 - 15:03):** <https://polyscience.com/circulating-baths/28-liter-heated-circulator-3>