

28 Liter Stainless Steel Open Bath System



MX28S135

Key Specifications

Description	28 L Open Bath System
Controller Type	MX
Display	3.25" LCD
Languages Supported	English
Working Temperature Range °C	Ambient +10° to 135°
Temperature Stability °C	±0.07°
Temperature Calibration Capability	1-point
Working Access (L x W x D) (cm)	25.7 x 21.4 x 20.3 cm
Pump Type	Pressure
Flammability Class (DIN 12876-1)	I (NFL)

Key Features

STAINLESS STEEL OPEN BATHS

Features

- Working temperatures from ambient +10° up to 150°C

- Advanced Programmable, Advanced Digital or MX Temperature Controller
- 6, 10, 20 or 28 liter reservoir
- DuraTop™ Chemical Resistant Bridge, Swivel 180™ Rotating Controller (on Advanced Programmable and Advanced Digital models)
- Lidded opening for optional cooling coil (10, 20 and 28 liter models)
- External circulation capability
- Complies with DIN 12876-1 Class I safety requirements for use with non-flammable liquids
- Includes bath cover

Select a Controller

	<u>Advanced Programmable (AP)</u>	<u>Advanced Digital (AD)</u>	<u>MX</u>
Temperature Stability	±0.005°C	±0.01°C	±0.07°C
Pump Type	Pressure/Suction, Variable-Speed	Pressure/Suction, Variable-Speed	Pressure Only, 1-Speed
Programmability	Unlimited programs and steps	N/A	N/A
Connectivity	USB-A & B, Ethernet, RS-232/RS-485, Remote On/Off, External Temperature Probe	USB-A & B, Ethernet, RS-232/RS-485, External Temperature Probe	N/A

Select a Reservoir

	<u>6 Liter</u>	<u>10 Liter</u>	<u>20 Liter</u>	
Maximum Temperature	Advanced Programmable: 150°C Advanced Digital: 150°C MX: 135°C	Advanced Programmable: 150°C Advanced Digital: 150°C MX: 135°C	Advanced Programmable: 150°C Advanced Digital: 150°C MX: 135°C	Advanced Programmable: 150°C Advanced Digital: 150°C MX: 135°C
Working Access (L x W x H)	3.9 x 4.3 x 6 in 10 x 11 x 15.2 cm	3.9 x 10.1 x 6 in 9.9 x 25.5 x 15.2 cm	10.4 x 9 x 6 in 26.4 x 22.8 x 15.2 cm	10.1 x 8 25.7 x 2

Common Specifications

Working Temperature Range °F	Ambient +20° to 275°
Working Temperature Range °C	Ambient +10° to 135°
Reservoir Capacity (gallons)	7.4
Reservoir Capacity (liters)	28
Reservoir/Tank Material	Stainless Steel

Reservoir Cover	Included
DuraTop	Yes
Working Access (L x W x D) (inches)	10.1 x 8.4 x 8 in
Working Access (L x W x D) (cm)	25.7 x 21.4 x 20.3 cm
Temperature Stability °F	±0.13°
Temperature Stability °C	±0.07°
Display	3.25" LCD
Display Resolution (Set)	0.1
Display Resolution (Read)	0.1
Pump Type	Pressure
Pump Speed	One
Process Connections	1/2" O.D. Barbed Tubes
Flammability Class (DIN 12876-1)	I (NFL)
Over-Temperature Protection / Failsafe Heater Control	Yes
Low Liquid Level Protection	Yes
Cooling Coil	Accessory
Maximum Ambient Temperature °F	95°
Maximum Ambient Temperature °C	35°
Overall Dimensions (L x W x H) (inches)	20.9 x 13.5 x 18 in
Overall Dimensions (L x W x H) (cm)	53.1 x 34.2 x 45.7 cm
Environmental Compliance	RoHS, WEEE
Shipping Weight (pounds)	66.0
Shipping Weight (kilograms)	29.9
Catalog Page Number	62-63

60 Hz Only

Part Number	MX28S135-A11B
Maximum Pressure (psi)	2.3
Maximum Pressure (bar)	0.16
Maximum Pressure Flow Rate (gpm)	3.60
Maximum Pressure Flow Rate (l/min)	13.5
Included Hardware	Fitting Kit for External Applications
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	120/60/1/10
Regulatory Approvals	ETL

50 Hz Only

Part Number	MX28S135-A12E
Maximum Pressure (psi)	1.8
Maximum Pressure (bar)	0.12

Maximum Pressure Flow Rate (gpm)	3.10
Maximum Pressure Flow Rate (l/min)	11.9
Included Hardware	Fitting Kit for External Applications
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	240/50/1/6
Regulatory Approvals	CE



© 2015-2020 **PolyScience** 6600 W. Touhy Avenue, Niles, Illinois 60714-4516 USA

Phone: +1(847) 647-0611 or +1(800) 229-7569 **Fax:** +1(847) 647-1155

*/

Source URL (modified on 09/16/2020 - 07:51): <https://polyscience.com/circulating-baths/28-liter-stainless-steel-open-bath-system-1>