

# Cryoprecipitate Bath

**Image:**



## Key Specifications

<b>Description</b>	Cryoprecipitate Bath
<b>Controller Type</b>	Digital
<b>Display</b>	Two Digital Readouts
<b>Working Temperature Range °C</b>	Setpoint Fixed@ 4°C (For a Variable Setpoint option, please contact Sales)
<b>Temperature Stability °C</b>	±0.1°
<b>Temperature Calibration Capability</b>	1-point
<b>Working Access (L x W x D) (cm)</b>	52.4 x 33 x 30.5 cm

# Key Features

## CRYOPRECIPITATE BATH

### Features

- Setpoint Fixed at 4°C (Variable Setpoint 4° to 40°C on -V models)
- Thaws up to 24 units of FFP or Whole Blood (WB) simultaneously
- Bright temperature and elapsed time displays
- Built-in over-temperature and flow alarms
- Calibration capability
- High efficiency fluid filter, removable air filter, reservoir drain
- Hinged polycarbonate gabled cover
- 20 slot thawing rack
- RS232 included on variable temperature -V models

### Common Specifications

<b>Working Temperature Range °C</b>	Setpoint Fixed@ 4°C (For a Variable Setpoint option, please contact Sales)
<b>Reservoir Capacity (gallons)</b>	13.8
<b>Reservoir Capacity (liters)</b>	52.24
<b>Reservoir/Tank Material</b>	Stainless Steel
<b>Reservoir Cover</b>	Included
<b>Cleanable Air Filter</b>	Yes
<b>Working Access (L x W x D) (inches)</b>	20.6 x 13 x 12 in
<b>Working Access (L x W x D) (cm)</b>	52.4 x 33 x 30.5 cm
<b>Temperature Stability °F</b>	±0.2°
<b>Temperature Stability °C</b>	±0.1°
<b>Display</b>	Two Digital Readouts
<b>Display Resolution (Set)</b>	0.1
<b>Display Resolution (Read)</b>	0.1
<b>Over-Temperature Protection / Failsafe</b>	Yes
<b>Heater Control</b>	Yes
<b>Low Liquid Level Protection</b>	Yes
<b>Reservoir Drain</b>	Yes
<b>Maximum Ambient Temperature °F</b>	95°
<b>Maximum Ambient Temperature °C</b>	35°
<b>Overall Dimensions (L x W x H) (inches)</b>	28 x 14.5 x 36.6 in
<b>Overall Dimensions (L x W x H) (cm)</b>	71.1 x 37 x 93 cm
<b>Shipping Weight (pounds)</b>	200.0

Shipping Weight (kilograms)	90.7
Catalog Page Number	75

## 50 Hz Only

Part Number	6250MYCRY30E / 6250MYCRY30E-V
Electrical Requirements (VAC/Hz/Ph/A)	240/50/1/9.0
Regulatory Approvals	CE

## 60 Hz Only

Part Number	6260MXCRY10C / 6260MXCRY10C-V
Electrical Requirements (VAC/Hz/Ph/A)	120/60/1/11.25
Regulatory Approvals	TUV



© 2015-2020 **PolyScience** 6600 W. Touhy Avenue, Niles, Illinois 60714-4516 USA

**Phone:** +1(847) 647-0611 or +1(800) 229-7569 **Fax:** +1(847) 647-1155

\*/  
**Source URL (modified on 05/06/2020 - 14:57):** <https://polyscience.com/specialty-product/cryoprecipitate-bath>